

Evaluation of Volitional Entry and Passage of Adult Pacific Salmonids through a Novel Fish Passage Technology

BRIAN J. BELLGRAPH, ALISON H. COLOTELO, TIM J. LINLEY, LYSEL J. GARAVELLI, BRIANA M. RHODE, JILL M. JANAK

Pacific Northwest National Laboratory

Status of Whooshh Research to National Marine Fisheries Service, Portland, Oregon, 20 August 2018







- Publication in Review: Garavelli, L.J., T.J. Linley, B.J. Bellgraph, B.M. Rhode, J.M. Janak, and A.H. Colotelo. In Review. Evaluation of Volitional Entry and Passage of Adult Pacific Salmonids Through a Novel Fish Passage Technology. Submitted to Fisheries Research.
- Introduction
 - Background and Objectives
- Methods
 - Study Site Setup
 - Experimental Procedure
 - Fish Assessment
 - Analysis
- Results
- Discussion, Caveats, Next Steps

Introduction



Problem(s):

- 1. U.S. Department of Energy (DOE) mission to improve sustainability of energy generation while reducing environmental effects e.g., improve fish passage to reduce effects of hydropower
- 2. Whooshh Innovations goal to advance understanding of their technology to meet NMFS experimental fish passage approval process

Solution:

Through DOE's Small Business Voucher Program, Whooshh won grant to advance commercialization of their newest volitional entry system and work toward DOE's energy/environmental mission by evaluating newest version of the WFTS.

Publication Study Objectives:

- 1. Investigate the feasibility of volitional entry and passage of adult Chinook salmon and steelhead
- 2. Assess its effects on fish during their passage through the system

Study Site



- Ringold Springs Rearing Facility (Columbia River – Hanford Reach)
 - Fall Chinook salmon and steelhead return to hatchery via Ringold Springs
 - Swim 200 m upstream to a V-trap weir, then trapped within a collection pool



WFTS Setup



- Enter an Alaskan steeppass fishway volitionally
- Pass through a 'flow box' and false weir into camera chamber (Whooshh-Ellips Sorting System, WESS)
- Either diverted back to collection pool via bypass, or transported to an exit pool via Whooshh tube



Experimental Overview





Reduced from 3 treatments due to low fish numbers

8 sampling days from 2 Oct – 7 Nov 2017

Low density required crowding fish to encourage passage

Study analysis performed relative to manually measured gir
 85% body occlusion for WFTS transport (i.e., ~400 mm girth)
 Based on length, width, height, girth

- Girth > 400 mm → WFTS tube
- Girth < 400 mm → Bypass</p>
- If < 0.5 seconds between fish, default to Bypass

Exit pools:


WFTS tube: 5 m long, 2.5 m wide, 1 m deep
Bypass: 1.3 m long, 0.6 m wide, 0.8 m deep

Visual Assessment of both Treatments



Experimental Schematic





Fish Assessment and Analysis



Assessment:

- Sedated with 15 ppm Aqui-S 20E until Stage 4 anesthesia (about 2-3 minutes)
- For Chinook: length, girth, mass, sex, fungus cover, and overall external body condition
- For Steelhead: girth, condition, and sex
- Chinook transferred to hatchery raceway; Steelhead back to Columbia River

Unexpected Events:

- Backward transport
- Temporary stalling
- Other

Analysis:

- Differences in girth, length, and mass between WFTS tube, Bypass, and Control using Kruskal-Wallis ranks
- Pairwise comparisons using Dwass-Steel-Critchlow-Flinger test with alpha = 0.05


Fish girth (mm)

Results

- Scanned & Sorted: 298 Chinook, 85 Steelhead
 - 75% (n=225) of Chinook Tube-transported
 - 93% (n=79) of Steelhead Bypassed
- Control: 69 Chinook; no steelhead due to WDFW regulation

Sorting:

- Girth, length, and mass all significantly greater for transported fish compared to bypassed fish (W≥ 60.8, p < 0.001) and control fish (W≥ 58.2, p < 0.001)
- Length and mass differed significantly between bypassed and control Chinook ($W \ge 6.7$, p < 0.001); girth did not ($W \ge 1.3$, p = 0.62)
- 400 mm girth-defined criteria:
 - < 400 mm: 127 Tube-transported (1 Steelhead)</p>
 - > 400 mm: 12 Bypassed (all Chinook)





Results



- Injury Assessment:
 - Chinook: only hemorrhaging of fins and eyes (n = 11)
 - Hemorrhaging in 6 of 225 Tube-transported (2.7%), 1 of 73
 Bypassed (1.4%) , and 4 of 69 Controls (5.8%)
 Only one mortality
 - 47 Unexpected Events:
 - **35** backwards transport
 - 8 temporarily stalled
 - 3 backwards and temporarily stalled
 - 1 error setup of Tube



Discussion



- Sorting generally distinguished fish size
 - 400 mm not a 'hard' criteria
 - Default to Bypass safety mechanism
 - Most (n = 118) Tube-transported Chinook < 400 mm passed normally; 8 temporarily stalled
- No injury difference vs. Controls
 - Minor and observed less than Control group
 - Suggests long-term or population effects likely minimal
- Unexpected Events are manageable:
 Low for both Chinook salmon and steelhead
 Higher rate observed when 2 or more fish entered the system in close proximity




Caveats and Next Steps



- Volitional entry facilitated by addition of steeppass, which required a series of behavioral events (i.e., detection, entry, ascent) to occur prior to fish encountering the WESS-WFTS
- Study limited to single tube

Next Steps:

- Ideal Study: Directly compare performance of WESS-WFTS to conventional fishway
- In-progress: Address factors that lead to unexpected events
 - Sensing stalls and autonomously adjusting blower settings to address the stall)
 - Reduce backwards transport



Acknowledgments



- We thank staff with the Washington Department of Fish and Wildlife's Ringold Springs Hatchery for their help conducting the study
- We also thank Erin McCann and Bernardo Beirao at PNNL for assisting in data collection.
- Lastly, we thank the entire staff of Whooshh Innovations for their help teaching us how to operate and troubleshoot the updated prototype WFTS.

Questions?